

COMPACT10E

Modular and high performing vacuum ejector









Overview

COMPACT10E - a new vacuum ejector/pump family where Piab's new recognized and reliable technologies remain high-performing and energy efficient yet are easy to maintain, modular, and cost competitive.



Single unit width 10mm



Single unit* weight < 85 g



Max Vacuum 91 -kPa**



Low noice level



Push-in connectors

*) Vacuum Sensor excluded.

**) Xi2.5 COAX® ejector nozzle

Thanks to the compact size and light weight, the COMPACT10E can easily be installed near Piab's suction cups without interfering with motion of the robot. This improves the vacuum performance and the ability to run the machine even faster than before. The COMPACT10E is made to be modular and robust, which minimizes the need for services parts such as vacuum filters and ejector nozzles and instead maximizes machine uptime.

- **Manifolds** with up to 8 units, common feed pressure port for easy and compact installation.
- Integrated vacuum switch, direct operating high speed valves, vacuum filters and ejector nozzles.
- Selection of different multi-stage ejector characteristics to optimize for the application needs (flow/speed, vacuum level and air feedpressure).
- Design perfectly suitable for clean room applications where also exhaust from valves are collected.
- Adjustable release flow to further help improve cycle times.
- Easy trouble shooting. A Single unit is fast removed from the manifold. All service points easy accessible.

Features

Vacuum ejector/nozzle

COAX® Micro characteristics.
Xi – Extra vacuum level (X)

Ti – Extra high vacuum flow (T)

Valves

Vacuum and Blow-Off valves.

Blow-Off needle valve

Easy setting of the Blow-Off flow.

Manifold

Stacked 2 – 8 units with central compressed air feed configurable with central silencer or central

exhaust (12mm stem).

Silencer
Integrated and compact silencer for single units or a central exhaust for

single units or a central exhaust for clean room requirements. Manifold mounted units come with a central and efficient silencer or an exhaust stem to pipe away the air.

Vacuum sensing

Select an integrated user friendly vacuum switch with display, or just a unit with a sensing port for vacuum.

7 Vacuum filter
Cleanable and replaceable vacuum filter.

Push-in Connectors
Configurable with push-in connectors 4 mm or 6 mm (not on exhaust).

Contact
www.piab.com